

Server Case Product 1U

1U4Bay Hot-swappable Cases



1 Feature and Benefits:

- 1 Made of imported 1.2mm refined SGCC galvanized materials, surface smooth and shiny
- 2 1U rack server cases, depth is 660mm
- 3 Support 4 pieces of 3.5 inch or 2.5 inch disk hot plug.
- 4 Cases backplane transmission rate of 6 GB/s, the hard disk support alarm function (SGPIO signal)
- 5 4X 4028 hot swap fan, speed up to 13000 rpm
- 6 Support 1 transverse high card slot
- 7 Standard 19 inch rack installation

Core backplane descriptions

1 The use of dual redundant power supply system (any interface in two large 4Pin power interfaces connected to the power, the backplane can work stable)

- 2 Intelligent temperature control system design of backplane
- 3 The backplane comes with temperature sensors

CASES DATA SHEET



2 Technical Parameters:

Cases Style	Rack
Cases Type	IU4bay
Compatible board size	550*435*45 ATX (12" x13")
Compatible motherboard brand	INTEL, Asus, Supermicro, Tyan, MSI, Gigabyte, etc.
Front panel instructions	2XUSB,1XPower button, 1XReset button, 1XPower LED, 1X HDD LED and 2XNetwork LEDs
Support Power type	1U single power
Support Power Quantity	1PCS
Drive bays	Four 3.5-inch or 2.5-inch hard drives
CD-ROM drive	1 PCS notebook CD-ROM drive
HDD Backplane	6GB SAS backplane compatible SATA
Hot-swappable fans	Supported
Cooling System	Standard configuration with 4 branded 4028 fans, each
	fan reaching rpm of 13,000.
Expansion card slots	One full-height PCI
Intelligent temperature control	Supported
Hard disk shock proof	The shockproof fan reduces the resonance between the
	fan and the hard disk, and does not affect the read-write
	speed of the hard disk
Slide way Support	Optional
SGPIO	Optional
Material	Imported SGCC (galvanized sheet)
	Imported SGCC (galvanized sheet) Not Supported
Power cut when lid is opened	Not Supported
Power cut when lid is opened Cases Dimensions	Not Supported 660 (L) X 434(W) X 45(H) ,26" X 17" X 1.7"