

Server Case Product 2U 2U12Bay Hot-swappable Cases



1 Feature and Benefits:

- 1 Made of imported 1.2mm refined SGCC galvanized materials, surface smooth and shiny
- 2 2U rack server cases, depth is 650mm
- 3 Support 12 pieces of 3.5 inch or 2.5 inch disk hot plug.
- 4 Case backplane transmission rate of 6 GB/s, the hard disk support alarm function (SGPIO signal)
- 5 4X 8025 hot swap fan, speed up to 4,500 rpm
- 6 Support 7 half-height PCI-E expansion cards
- 7 Standard 19 inch rack installation

Core backplane descriptions

- 1 The use of dual redundant power supply system (any interface from two large 4Pin power interfaces connected to the power, the backplane can work stable)
- 2 Intelligent temperature control system design of backplane
- 3 The backplane comes with temperature sensors

CASES DATA SHEET



2 Technical Parameters:

Cases Style	Rack
Cases Type	2U12bay
Compatible board size	Extended ATX (12" x 13")
Compatible motherboard brand Front panel instructions	INTEL Asus, Supermicro, Tyan, MSI, Gigabyte, etc 2XUSB,1XPower button, 1XReset button, 1XPower LED, 1 XHDD LED and 2XNetwork LEDs
Support Power type	1+1 redundant power, single power
Support Power Quantity	1PCS
Drive bays	Twelve 3.5-inch or 2.5-inch hot-swappable hard
CD-ROM drive	Not supported
HDD Backplane	6GB SAS backplane compatible SATA
Hot-swappable fans	Supported
Cooling System	Standard configuration with 4 branded 4028 fans,, each fan reached a speed of 4,500 rps
Expansion card slots	7 half-height PCI
Intelligent temperature control	Supported
Hard disk shock proof	The shockproof fan reduces the resonance between the fan and the hard disk, and does not affect the read-write speed of the hard disk
Slide way Support	Optional
SGPIO	Optional
Material	Imported SGCC (galvanized sheet)
Power cut when lid is opened	Supported
Cases Dimensions	650 (L) X 434(W) X 89(H) 25.5" X 17" X3.5"
Packing Dimensions	875(L)X635X(W)X195(H)mm
Net weight	11.1kg
Gross weight	14.7kg