

Server Case Product 4U 4U24Bay Hot-swappable Cases



1 Feature and Benefits:

- 1 Made of imported 1.2mm refined SGCC galvanized materials, surface smooth and shiny
- 2 4U rack server cases, depth is 650mm
- 3 Support 24 pieces of 3.5 inch or 2.5 inch disk hot plug and 2 built in hard disks
- 4 Case backplane transmission rate of 6 GB/s, the hard disk support alarm function (SGPIO signal)
- 5 4x 8025 hot swap fan, speed up to 4,500 rpm
- 6 Support 7 half-height PCI-E expansion cards
- 7 It is also compatible with standard 2U standard power supply, 1+1 redundant power supply and 2+1 redundant power supply
- 8 Standard 19 inch rack installation

Core backplane descriptions

- 1 The use of dual redundant power supply system (any interface from two large 4Pin power interfaces connected to the power, the backplane can work stable)
- 2 Intelligent temperature control system design of backplane
- 3 The backplane comes with temperature sensors

CASES DATA SHEET



2 Technical Parameters:

0 0 1	
Cases Style	Rack
Cases Type	4U24bay
Compatible board	
size	Extended ATX (12" x13")
Compatible	
	INTEL, Asus, Supermicro, Tyan, MSI, Gigabyte, etc.
Front panel instructions	2XUSB,IXPower button, 1XReset button, 1XPower LED, 1 XHDD LED and 2XNetwork LEDs
Support Power type	1+1 redundant power, 2+1 redundant power, single power
Support Power Quantity	1PCS
Drive bays	Twenty-four 3.5-inch or 2.5-inch hard drives
CD-ROM drive	Not Supported
HDD Backplane	6GB SAS backplane compatible SATA
Hot-swappable fans	Supported
Cooling System	Standard configuration with 4 branded 8025 fans, each fan reached a speed of 4,500 rps
Expansion card slots	7 full-height PCI or PCI-E
Intelligent temperature control	Supported
Hard disk shock proof	The shockproof fan reduces the resonance between the fan and the hard disk, and does not affect the read-write speed of the hard disk
Slide way Support	Optional
SGPIO	Optional
Material	Imported SGCC (galvanized sheet)
Power cut when lid is opened	Supported
Cases Dimensions	650(L)X434(W))X177(H)mm
Packing Dimensions	875(L)X635X(W)X285(H)mm
Net weight	17.9kg
Gross weight	21.9kg