

# TX7210

## Addressable Single Input/Output Module



### 1 Feature and Benefits

- EN54-18 Compliance
- Built-in MCU processor and digital addressing
- 24Vdc/3A Output relay contact and Control module Input Fire or Supervisory signal configuration
- Input Fire or Supervisory signal configuration
- LED status indicator
- Onsite Adjustable Parameter
- Loop or external power input
- Aesthetically pleasing design
- Surface mounting with fix base for simple installation

### 2 Technical Specification

- Compliance EN54-18:2005/AC2007
- Input Voltage Loop Power:24VDC [16V to 28V] External PSU: 20 to 28VDC
- Current Consumption Loop: Standby 0.6mA, Alarm: 1.6mA External PSU: Standby 0.6mA, Alarm: 45mA
- Control output voltage 24VDC / 3A rating
- Input Relay Normally Open dry contact
- Input Resistance 5.1Kohms/ ¼ W
- Protocol/Addressing TNA, Value range from 1 to 254
- Indicator Status Normal: Single blink/Active: Steady/Fault: Double Blink
- Material / Colour ABS / White Glossy finishing
- Dimension / LWH 108 mm x 86 mm x38 mm
- Weight 170g (with Base), 92g (without Base)
- Operating Temperature -10°C to +50°C
- Ingress Protection Rating IP30
- Humidity 0 to 95% Relative Humidity, Non condensing

# TX7 DATA SHEET

---