

FIRE ISOLATOR

Datasheet FireBlanket Ultimate VR0906Li

Product description

The T-ISS FireBlanket Ultimate can be used for normal, combustion-engined and EV car fires. It can be deployed in parking garages, parking lots, shopping malls, onboard ferries, etc. The blanket can be used for all car sizes from a small city car up to large SUV models.

Due to depriving the oxygen inlet, the car fire will be isolated. The fire will not spread and will avoid collateral damage, also the smoke spread will stop and gives fire crews easier access to the vehicle.

The FireBlanket is reusable and can be cleaned. It can stand peak temperatures of 1600 °C, and can withstand 1200 °C for more than 50 hours. The FireBlanket Ultimate VR0906 Li is easy to deploy by 2 people.

Pictures



Dimensions & Specifications

Art. No: VR0906Li FireBlanket Ultimate
Size: 900 x 600 cm
Weight: 37 kg
Material: Silica grade, eco friendly
Temperature: + 1600 °C tested
Tests: ASTM D6413
Tested according to ISO EN 13501-1

Suitable for Combustion & Lithium powered Vehicles. The fire blanket can withstand very high temperatures but does not stand up well to sharp objects or overly rough handling of the blanket. The installation of the blanket must therefore be done carefully, without hard, jerky movements, so as not to damage the fabric or the loops.

HS code: 7019 9000 85

Pictures



Options

- Supplied in sturdy bag
- Cabinet available
- Big buons that are easy to control
- Bright white so it's always easy to recognize if there are cracks
- Suitable from small cars to large Pickups

Pictures



Visit our website:

FIREISOLATOR.COM

© COPYRIGHT T-ISS B.V. - All rights reserved

T-ISS
Safety Suppliers

Global

Studsgaard

Scandinavia

GARANT
ProTech

Baltic, Russia, Finland, Poland